


- CAT8 Class I RJ45 plug to be assembled in the field
- FTP TYPE: 1 piece Design
 - Easy Assembly - easily terminated in the field in 2 minute without any special tools
 - Wire Connection: Stranded wire AWG 27/7 to 22/7, wire diameter from 0.46 to 0.76 mm
 - Wire Connection: Solid wire AWG 26/1 to 22/1, wire diameter from 0.4 to 0.76 mm
 - it Suitable according to IEEE 802.3an
 - Suitable for Power over Ethernet(PoE, PoE plus, and UPoE)
 - Cable Jacket Diameter from 6 to 9.5 mm
 - Adjustable Strain Relief (6mm to 9.5mm Cable OD)
 - Load Bar for Faster and Easier Wire Pattern Termination
 - Reconnectable

- Operation temperature:-40°C to 60°C, Relative humidity: 85%(30°C), Air pressure: 70-106kpa.
- Gold Plated Phosphor Bronze Blade: phosphor bronze and gold plating (3~50inch), mating durability not less than 750 cycles :
- Anti-burn performance: product made from Kirsite \ PC or PCB(UL94V-0), meeting the international standard :
- Intermediate resistance: no more than 20m ohm in normal atmosphere pressure (not including bulk resistor) :
- Insulated resistance: no less than 1,000M ohm in normal atmosphere pressure :
- Intensity of anti-currency: DC 1,000V (AC:700V), no puncture and flash-over phenomenon in one minute :
- Retention strength: 7.7kg between jack and plug.
- Label: clear label to ensure easy to management :



TITLE:		INCH		MM	
.X	.015	.30			
.XX	.010	.10			
.XXX	.005	.05			
DRAWN BY	MA	P/N:	SCALE	1:1	
CHECK BY		UNIT	MM		REV
APPD BY		SHEET	1/1		
		DATE	2019/01/10	DWG	ND: